



RGB+PLUS Line Cubes - 24Vdc

RGB+C100-24, C250-24, C300-24, C350-24, C400-24

Sizes: 100, 250, 300, 350 & 400mm /
4-inch, 10", 12" 14" & 16"

Wire Color: black, green, white

Output	
LED Type	SMD 5050
LED Channels	R-G-B
LED Count	4, 20, 24, 28 & 32, respectively
Greyscale	16-bit, 65,536 dimming levels*
Viewing Angle	360-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+3, MeshTek
Max Lamps before power injection	approx. 20-45L (depending on size & spacers)
Max Distance before Power Injection	approx. 150-feet
Electrical & Safety	
Input Voltage	24 VDC
Current	0.02, 0.085, 0.110, 0.135, 0.165 Amps / lamp, respectively
Power	0.5, 2, 2.7, 3.3, 4 Watts / lamp, respectively
Wire	22 AWG, 4C, UV protected ; 3W T-way (100mm = 22 AWG, 3C, UV)
Inline power injection	via Minleon Power T+'s & RGB+3A/4A-24V
Certifications	IP 65 (when ground mounted)
Physical	
Diameter (mm)	100, 250, 300, 350, 400mm // 4-inch, 10", 12" 14" & 16", respectively
Size	6 options listed above
Weight (kg)	approx. 0.09, 0.843, 1.052, 1.34, 1.747kg // 0.2, 2.0, 2.5, 3.0 & 4.0 lb., respectively
Housing	polycarbonate
Connector Type	LLT twist-lock
Lead/End Wire length	36" (standard)
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com

* 8-bit via DDP.

Specifications as of Aug. 2024 and are subject to change.

